


# ➔ Projektor Pro G3



➔10W ➔20W ➔30W ➔50W ➔100W ➔150W ➔200W

LANÇAMENTO

# Projektor Pro G3 ←



Dimensões			
	A	B	C
10W	26mm	125mm	104mm
20W	28mm	149mm	125mm
30W	30,3mm	168mm	209mm
50W	36mm	200mm	237mm
100W	38mm	277mm	321mm
150W	52mm	332mm	395mm
200W	52mm	382mm	455mm

Código	Potência	Temperatura de Cor	Fluxo Luminoso	Código de Barras	Caixa
11346	10W	3.000K	800lm	7899710010958	36 unid.
11347	10W	6.500K	800lm	7899710010965	36 unid.
11348	20W	3.000K	1.600lm	7899710010972	30 unid.
11349	20W	6.500K	1.600lm	7899710010989	30 unid.
11350	30W	3.000K	2.400lm	7899710010996	20 unid.
11351	30W	6.500K	2.400lm	7899710011009	20 unid.
11352	50W	3.000K	4.000lm	7899710011016	12 unid.
11353	50W	6.500K	4.000lm	7899710011023	12 unid.
11354	100W	6.500K	7.500lm	7899710011030	4 unid.
11355	150W	6.500K	11.250lm	7899710011047	3 unid.
11356	200W	6.500K	15.000lm	7899710011054	2 unid.
11953	10W	3000K	800lm	7899710012730	36 unid.
11954	10W	6500K	800lm	7899710012747	36 unid.
11955	20W	3000K	1.600lm	7899710012754	30 unid.
11956	20W	6500K	1.600lm	7899710012761	30 unid.
11957	30W	3000K	2.400lm	7899710012778	20 unid.
11958	30W	6500K	2.400lm	7899710012785	20 unid.
11959	50W	3000K	4.000lm	7899710012792	12 unid.
11960	50W	6500K	4.000lm	7899710012808	12 unid.

MULTITENSÃO  
100-240V

VIDA ÚTIL (L70)  
25.000h

GRAU DE PROTEÇÃO  
IP65\*

ÂNGULO DE  
ABERTURA 120°

\*Totalmente protegido contra a poeira. Protegido contra jatos de água.